

HART 7 temperature converter, loop-powered

3337

- High accuracy, better than 0.05% of span
- Slimline housing of 6.1 mm
- Excellent EMC performance
- Selectable 60 ms / 60 s response time
- Pre-calibrated temperature ranges selectable via DIP-switches



Application

- The 3337 temperature converter measures a standard Pt100, TC J and K temperature sensor, and provides an isolated passive analog current and HART signal output.
- High 2 port isolation provides surge suppression and protects the control system from transients and noise.
- The 3337 can be mounted in the safe area or in Zone 2 / Division 2 areas.
- Approved for marine applications.


Technical characteristics

- Flexibly loop powered by 6.2...35 VDC via connectors. A 60 ms fast response time with simultaneous sensor error detection when selected.
- Selectable internal/external CJC. Excellent conversion accuracy in all available ranges, better than 0.05% of span.
- Meeting the NAMUR NE21 recommendations, the 3337 provides top measurement performance in harsh EMC environments.
- The device meets the NAMUR NE43 standard defining out of range and sensor error output values.
- All terminals are protected against overvoltage and polarity error.
- High galvanic isolation of 2.5 kVAC.
- Excellent signal/noise ratio of > 60 dB.


Mounting / installation

- Selectable HART mode with HART 7 revision protocol enables extended device programming.
- Selectable DIP-mode for easy configuration of more than 1000 factory calibrated measurement ranges with HART read only feature.
- Selectable HART-mode to enable full HART read-write capability.
- The narrow 6.1 mm housing allows up to 165 units to be mounted per meter of DIN rail, without any air gap between units.
- Wide ambient temperature range of -25...+70°C.

Application



**Safe Area or
Zone 2 & Cl. 1, Div. 2, gr. A-D**



Order

Type
3337

Environmental Conditions

Operating temperature	: -25°C to +70°C
Storage temperature	: -40°C to +85°C
Calibration temperature	: 20...28°C
Relative humidity	: < 95% RH (non-cond.)
Protection degree	: IP20
Installation in	: Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)	: 113 x 6.1 x 115 mm
Weight approx	: 70 g
DIN rail type	: DIN EN 60715/35 mm
Wire size	: 0.13...2.5 mm ² / AWG 26...12 stranded wire
Screw terminal torque	: 0.5 Nm
Vibration	: IEC 60068-2-6
2...25 Hz	: ±1.6 mm
25...100 Hz	: ±4 g

Common specifications

Supply

Supply voltage	: 6.2...35 VDC
Max. required power	: 0.80 W
Internal power dissipation	: 22 mW...0.8 W

Isolation voltage

Isolation voltage, test / workin	: 2.5 kVAC / 55 VA (reinforced)
Zone 2 / Div. 2	: 250 VAC

Response time

HART mode, (0...90%, 100...10%)	: 60 ms...60 s, programmable
DIP mode, (0...90%, 100...10%)	: < 60 ms

Voltage drop	: 6.2 VDC
Signal / noise ratio	: Min. 60 dB
Programming	: DIP-switches
Signal dynamics, input	: 23 bit
Signal dynamics, output	: 18 bit
EMC immunity influence	: < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst	: < ±1% of span
Incorrect DIP-switch setting identification	: 3.5 mA

Input specifications

RTD input

Temperature range, Pt100	: -200...+850°C
Min. measurement range (span)	: 10°C
Accuracy: the greater of	: Better than 0.05% of span or 0.1°C
Temperature coefficient: the greater of	: 0.02°C/°C or ≤ ±0.01%/°C
Sensor current	: < 150 µA
Sensor cable resistance	: < 50 Ω per wire

Effect of sensor cable resistance (3-/4-wire)	: < 0.002 Ω / Ω
Sensor error detection	: Yes - selectable via DIPswitch

Broken sensor detection	: > 800 Ω
Shorted sensor detection	: < 18 Ω

TC input

Temperature range, TC J	: -100...+1200°C
Temperature range, TC K	: -180...+1372°C
Accuracy: the greater of	: Better than 0.05% of span or 0.5°C
Temperature coefficient: the greater of	: 0.1°C/°C or ≤ ±0.01%/°C
Sensor cable resistance	: < 5 kΩ per wire
Cold junction compensation (CJC): Accuracy @ external Pt100 input	: Better than ±0.15°C
Cold junction compensation (CJC): Accuracy @ internal CJC	: Better than ±2.5°C
Internal CJC error detectio	: Yes
External CJC error detection	: Yes - selectable via DIPs witch
Open Thermocouple detection	: Yes - selectable via DIP switch

Output specifications

Common output specifications

Updating time	: 10 ms
Current output	
Programmable signal ranges	: 4...20 and 20...4 mA
Load (@ current output)	: ≤ (Vsupply - 5.5) / 0.023 [Ω]
Load stability	: ≤ 0.01% of span / 100 Ω
Sensor error indication	: 3.5 mA or 23 mA / acc. to NAMUR NE43 or OFF
HART protocol revisions	: HART 7

I.S. / Ex marking

ATEX	: II 3 G Ex ec IIC T4 Gc
IECEx	: Ex ec IIC T4 Gc
FM, US	: Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, AEx nA IIC T4
FM, CA	: Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, Ex nA IIC T4
EAC Ex	: 2Ex nA IIC T4 Gc X

TEMPERATURE CONVERTER TRANSMITTER PR3337



Data sheet PR3337 | Edition 2023

Order

Type
3337

Observed authority requirements

EMC	: 2014/30/EU & UK SI 2016/1091
LVD	: 2014/35/EU & UK SI 2016/1101
ATEX	: 2014/34/EU & UK SI 2016/1107
RoHS	: 2011/65/EU & UK SI 2012/3032
EAC	: TR-CU 020/2011
EAC Ex	: TR-CU 012/2011

Approvals

ATEX	: KEMA 10ATEX0147 X
IECEX	: KEM 10.0068X
UKEX	: DEKRA 21UKEX0055X
c FM us	: FM17US0004X / FM17CA0003X
c UL us, UL 61010-1	: E314307
DNV Marine	: TAA00001RW
EAC Ex	: RU C-DK.HA65.B.00355/19