



## Universal transmitter

# 4114

- Input for RTD, TC, Ohm, potentiometer, mA and V
- 2-wire supply > 16 V
- FM-approved for installation in Div. 2
- Output for current and voltage
- Universal AC or DC supply



## Advanced features

- Programmable by way of detachable display front (PR 4500 series), process calibration, signal simulation, password protection, error diagnostics and help text available in several languages.

## Application


- Linearized, electronic temperature measurement with RTD or TC sensor.
- Conversion of linear resistance variation to a standard analog current / voltage signal, i.e. from solenoids and butterfly valves or linear movements with attached potentiometer.
- Power supply and signal isolator for 2-wire transmitters.
- Process control with standard analog output.
- Galvanic separation of analog signals and measurement of floating signals.
- The 4114 is designed according to strict safety requirements and is therefore suitable for application in SIL 2 installations.
- Suitable for the use in systems up to Performance Level "d" according to ISO-13849.

## Technical characteristics


- When 4114 is used with the PR 4500 display series, all operational parameters can be modified to suit any application. As the 4114 is designed with electronic hardware switches, it is not necessary to open the device for setting of DIP-switches.
- A green / red front LED indicates normal operation and malfunction.
- Continuous check of vital stored data for safety reasons.
- 3-port 2.3 kVAC galvanic isolation.

## Application


### Input signals:



### Output signals:



### Supply:



**Order**

Type
4114

**Environmental Conditions**

Operating temperature	: -20°C to +60°C
Storage temperature	: -20°C to +85°C
Calibration temperature	: 20...28°C
Relative humidity	: < 95% RH (non-cond.)
Protection degree	: IP20

**Mechanical specifications**

Dimensions (HxWxD)	: 109 x 23.5 x 104 mm
Weight approx	: 155 g
DIN rail type	: DIN EN 60715/35 mm
Wire size	: 0.13...2.08 mm <sup>2</sup> / AWG 26...14 stranded wire
Screw terminal torque	: 0.5 Nm
Vibration	: IEC 60068-2-6
2...13.2 Hz	: ±1 mm
13.2...100 Hz	: ±0.7 g

**Common specifications**

**Supply**

Supply voltage, universal	: 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse	: 400 mA SB / 250 VAC
Max. required power	: ≤ 2.0 W
Max. power dissipation	: ≤ 2.0 W

**Isolation voltage**

Isolation voltage, test / workin	: 2.3 kVAC / 250 VAC
----------------------------------	----------------------

**Response time**

Temperature input (0...90%, 100...10%)	: ≤ 1 s
mA / V input (0...90%, 100...10%)	: ≤ 400 ms

**Auxiliary supplies**

2-w. supply (term. 44...43)	: 25...16 VDC / 0...20 mA
Programming	: PR 4500 communication interfaces
Signal / noise ratio	: Min. 60 dB (0...100 kHz)
Accuracy	: Better than 0.1% of sel. range
EMC immunity influence	: < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst	: < ±1% of span

**Input specifications**

**RTD input**

RTD type	: Pt10/20/50/100/200/250; Pt300/400/500/1000; Ni50/100/120/1000; Cu10/20/50/100
Cable resistance per wire	: 50 Ω (max.)
Sensor current	: Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire)	: < 0.002 Ω / Ω
Sensor error detection	: Yes
Short circuit detection	: < 15 Ω

Linear resistance input	: 0 Ω...10000 Ω
Linear resistance min...max	: 0 Ω...10000 Ω
Potentiometer input	: 10 Ω...100 kΩ
Potentiometer min...max	: 10 Ω...100 kΩ

**TC input**

Thermocouple type	: B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC) via ext. sensor in 5910	: 20...28°C ≤ ±1°C, -20...20°C / 28...70°C ≤ 2°C
CJC via int. mounted sensor	: ±(2.0°C + 0.4°C * Δt)
Sensor error detection	: Yes
Sensor error current: When detecting / else	: Nom. 2 μA / 0 μA

**Current input**

Measurement range	: 0...23 mA
Programmable measurement ranges.	: 0...20 and 4...20 mA
Input resistance	: Nom. 20 Ω + PTC 50 Ω
Sensor error detection: Loop break 4...20 mA	: Yes

**Voltage input**

Measurement range	: 0...12 VDC
Programmable measurement ranges	: 0/0.2...1, 0/1...5, 0/2...10 VDC
Input resistance.	: Nom. 10 MΩ

**Output specifications**

**Current output**

Signal range	: 0...23 mA
Programmable signal ranges	: 0...20/4...20/20...0/20...4 mA
Load (@ current output)	: ≤ 800 Ω
Load stability	: ≤ 0.01% of span / 100 Ω
Sensor error indication	: 0 / 3.5 / 23 mA / none
NAMUR NE43 Upscale/Downscale	: 23 mA / 3.5 mA
Output limitation, on 4...20 and 20...4 mA signals	: 3.8...20.5 mA
Output limitation, on 0...20 and 20...0 mA signals	: 0...20.5 mA
Current limit	: ≤ 28 mA

**Voltage output**

Signal range	: 0...10 VDC
Programmable signal ranges.	: 0/0.2...1; 0/1...5; 0/2...10; 1
Load (@ voltage output)	: ≥ 500 kΩ
of span	: = of the presently selected range

# UNIVERSAL TRANSMITTER PR4114



Data sheet PR4114 | Edition 2023

## Order

Type
4114

## Observed authority requirements

EMC	: 2014/30/EU & UK SI 2016/1091
LVD	: 2014/35/EU & UK SI 2016/1101
RoHS	: 2011/65/EU & UK SI 2012/3032
ATEX	: 2014/34/EU
EAC	: TR-CU 020/2011
EAC LVD	: TR-CU 004/2011

## Approvals

c UL us, UL 508	: E231911
FM	: 3025177
DNV Marine	: TAA0000101
EU RO MR Type Approva	: MRA000000Z
SIL	: Hardware assessed for use in SIL applications